Professional Hearing Solutions

Latest Hearing Aids







DATA SHEET

www.professionalhearingsolution.com

0332-5014111

Volta P C

POWER-BTE WITH BATTERY SIZE 13



Audio Service

PRODUCT FEATURES

For closed fitting

BASIC FEATURES

- Battery compartment as on/off switch
- Push button, can be programmed as a program button, program button with on/off switch
- Rocker switch, can be programmed as volume control
- Level-dependent signal tones/melodies (activate/deactivate) for low battery voltage, program change, volume control, on/off function
- Telephone coil
- Audiomatic power-on delay (P) (activate/deactivate)
- Deformable earhook

OPTIONS

- Remote Control Smart Key
- Smart Remote App
- Audio shoe (transparent)

PROGRAMMING CABLES AND ADAPTER

Cable for HiPro interface, right	Art. No. 029 44 986
Cable for HiPro interface, left	Art. No. 029 44 994
Cable for Noah-Link interface, right	Art. No. 106 02 843
Cable for Noah-Link interface, left	Art. No. 106 02 842
Adapter 13	Art. No. 109 33 080

HOUSING COLORS

Beige Gray Dark brown

TECHNICAL FEATURES

- 8 signal processing channels / 4 frequency channels
- 4 AGC channels / 4 MPO channels
- 4 hearing programs
- Data Logging

SIGNAL PROCESSING

- Anti-Feedback system
- Noise Manager
  - › Adaptive noise reduction (on/off)
- AudioTronic multi-microphone system
  - › Directional static
- TRC S

ACCESSORIES

Clip for battery compartment in red and blue for side recognition

FITTING RANGE



P = Patent

For more information about features please check out our website www.audioservice.com

Volta P C

with earhook



Audio Service

	IEC 60118-7:2005[1] ANSI S3.22-2009[1]	IEC 60118-0[2]
MAXIMUM OUTPUT Input: 90 dB		
MAXIMUM GAIN Input: 50 dB		

TECHNICAL INFORMATION

		IEC 60118-7:2005[1] ANSI S3.22-2009[1]	IEC 60118-0[2]
MAXIMUM OUTPUT			
Peak value at 90 dB		134 dB	138 dB
1,600 Hz (RTF)		123 dB	132 dB
HFA (High Frequency Average)		126 dB	130 dB
FULL ON GAIN			
Peak value at 50 dB		70 dB	75 dB
1,600 Hz (RTF)		59 dB	67 dB
HFA (High Frequency Average)		62 dB	64 dB
Reference test gain		50 dB	60 dB
TECHNICAL FEATURES			
Battery type		13	13
Battery life in hours		145	145
Frequency range		110 – 6,000 Hz	170 – 6,700 Hz
Battery current consumption		1.4 mA	1.4 mA
Equivalent noise level		24 dB	24 dB
Telecoil sensitivity (1 mA/m)		93 dB	97 dB
Distortion	500 Hz	3%	4%
	800 Hz	2%	4%
	1,600 Hz	1%	1%

[1] Technical data measured in accordance with IEC 60118-7:2005 and ANSI S3.22-2009 at 2 ccm coupler
[2] Technical data measured in accordance with IEC 60118-0 at ear simulator

⚠ WARNING Small parts present a choking hazard.
This device is not suitable for fitting to babies, small children or mentally disabled persons.

⚠ WARNING The maximum output levels of the hearing systems can reach or exceed 132 dB SPL.
Risk of injury to the hearing of the wearer. Ensure that the hearing systems are fitted with care.

For control ranges and more programming features see Hearing Instrument Simulation of Connexx 8.3 and AudioFit 8.3 or higher.

AS AUDIO-SERVICE GmbH · Alter Postweg 190 · 32584 Löhne · Germany
info@audioservice.com · www.audioservice.com

06.2017 / Subject to change without prior notice. Color deviation possible due to printing process.